



# EloPOS Z10 for Android™

All-in-One POS System



Compact Form Factor



Android 10



Enterprise-Grade  
Support

## Product Overview

Built on Elo's unified architecture, the EloPOS Z10 delivers a powerful, minimalistic design to help optimize checkout in compact spaces without losing inches on your point-of-sale terminal. Complete with a 15.6-inch Full HD interactive display, I/O hub, contained cable routing, Android 10 OS and optional interactive customer-facing display, the EloPOS Z10 delivers one of the slimmest POS systems to the market.

Start changing the way customers and employees interact by deploying a new generation of interactive point-of-sale technologies that provide seamless integration, effortless provisioning and simplified device management via EloView or your preferred management tools.

Compatible with I-Series 4 Slate 15.6"  
full HD AiO touchscreen computer

Add Elo's 0702L Touchscreen Monitor to  
the back of the stand to create a point of  
interaction for customers

Enterprise-Grade Support - Security  
updates, seamless provisioning, Elo  
Home, OEMConfig and more

## EloPOS Z10 for Android

Specifications	
Bezel Color	Dark Grey Metallic
Diagonal Size	15.6" (396.24mm)
Operating System	Android 10 with Google Play Services and EloView content deployment and management
Processor	Standard: Qualcomm Snapdragon SDA660; Value: Rockchip RK3399
Memory	4GB
Storage	Standard: 64GB; Value: 32GB
I/O Ports	DC Input, 4 x USB-A 3.0 (900mA), RJ45 Ethernet LAN (Gigabit)
Compatibility	Compatible Display Head: I-Series 4 Slate Compatible Customer Facing Displays: 0702L - Elo P/N: E796382
Wireless	802.11a/b/g/n/ac + Bluetooth 5.0
Webcam	5MP, Max Resolution: 1920x1080 30fps, Auto Focus
Speakers	Standard: 2x 0.7W; Value: 2x 1W
Audio	Standard: 2x built-in Digital Microphones; Value: 1x built-in Analog Microphone
Active Display Area	13.55" x 7.62" / 344 mm x 194 mm
Resolution	1920 x 1080 @ 60Hz
Touch Technology	TouchPro® PCAP (Projected Capacitive) - up to 10 touches
Aspect Ratio	16:9
Number of Colors	8-bit (16.7M)
Brightness	LCD Panel: 350 nits; PCAP: 280 nits
Response Time	20 ms
Viewing Angle	Horizontal: ±85° or 170° total / Vertical: ±85° or 170° total
Contract Ratio	1000:1
Power	AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz
Power Consumption	Standard: On: 16W; Off: 0.4W; Sleep: 10.3W; Value: On: 10.3W; Off: 0.68W; Sleep: 4.4W
Real-Time Clock	Lithium coin cell battery
Dimensions (W x D x H)	I-Series 4 Slate Standard: 14.6" x 8.7" x 0.52" / 370.2 mm x 221.2 mm x 13.1 mm; Value: 14.6" x 8.74" x 0.55" / 370.8 mm x 221.8 mm x 13.95 mm Z10 POS Stand: 6.9" x 4.9" x 5.3" / 175 mm x 200.7 mm x 134.6 mm
Shipping Dimensions	I-Series 4 Slate: 17.44" x 12.20" x 6.14" / 443 mm x 310 mm x 156 mm; Z10 POS Stand: 8.19" x 11.8" x 11.2" / 208 mm x 300 mm x 285 mm
Weight	I-Series 4 Slate: 8.38 lbs / 3.8 kg; Z10 POS Stand: 3.63 lbs / 1.65 kg
Shipping Weight	I-Series 4 Slate: 12.13 lbs / 5.5 kg; Z10 POS Stand: 4.41 lbs / 2.0 kg
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)
Humidity	Operating: 20%-80%; Storage: 5%-95%
Mounting Options	VESA 75mm
MTBF	50,000 hours
Sealing	Touchscreen optically bonded to LCD
Warranty	2 years standard
Extended Warranty	POS stand - 3 year - Elo P/N: E375367, 4 year - Elo P/N: E375573, 5 year - Elo P/N: E375771, 2 year + AUR - Elo P/N: E375970, 3 year + AUR - Elo P/N: E376169, 4 year + AUR - Elo P/N: E376362, 5 year + AUR - Elo P/N: E376547 I-Series 4 Slate - 3 year - Elo P/N: E819394, 4 year - Elo P/N: E819598, 5 year - Elo P/N: E819795, 2 year + AUR - Elo P/N: E819985, 3 year + AUR - Elo P/N: E820186, 4 year + AUR - Elo P/N: E820388, 5 year + AUR - Elo P/N: E820582
Security Updates	Complimentary security updates provided for 3 months; Optional extended coverage available with EloCare OS 350 package
Regulatory Approvals	UL/cUL (US); FCC (US); IC (Canada); CE (Europe); CB (International); VCCI, MIC (Japan); RCM (Australia)
Supported Country List	Canada, USA, Australia, Japan, South Korea, New Zealand, Austria, Belgium, Czech Republic, Denmark, France, Germany, United Kingdom, Hungary, Italy, Netherlands, Poland, Portugal, Romania, Spain, Sweden, Switzerland, Turkey
What's in the Box	I-Series 4 Slate: IO Hub, NA Power Cable, EU Power Cable, 4 x M4x6 mm flathead screws, 4 x M4x6 mm panhead screws, CFD Mounting Cover, Power Brick 65W (E153026), QIG Z10 POS Stand: 4 x M4 screws for attaching head to stand, 4 x M4x18 screws for attaching an optional 0702L CFD display, CFD Mounting Cover, QIG

## Ordering Information

Family	Part Number	Size	Processor	Color	Memory	Storage
Standard	E391994	15.6-inch	Qualcomm Snapdragon SDA660	Dark Grey Metallic	4GB	64GB
Value	E392786	15.6-inch	Rockchip RK3399	Dark Grey Metallic		32GB
Z10 POS Stand	E398278	N/A	N/A	Dark Grey Metallic	N/A	N/A

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. Android is a trademark of Google LLC. Google Mobile Services is a trademark of Google LLC. All other trademarks are the property of their respective owners. © 2022 Elo Touch Solutions, Inc. All rights reserved. 22031AES00158

